

Dome B/W Camera



FEATURES

- 1/3" B/W CCD
- Minimum Illumination: 0.05Lux
- Horizontal Resolution: 420TV Lines
- Specification

Model	VC-315
Image Device	1/3" B/W CCD
TV System	PAL/NTSC
Effective Pixel	500(H) x 482(V)/510(H)x493(V)
Sync. System	Internal
Scanning System	2:1 Interlace
Grammer	r = 0.45
Scanning Frequency	Horizontal:15.625KHz Vertical:50Hz
Horizontal Resolution	420TV Lines
Minimum Illumination	0.05Lux F1.2
Video Output	1.0Vp-p VBS75Ω BNC
Gain	Built-in AGC 30dB; SAGC 36dB
S/N Ration	42dB
Electronic Shutter	1/50~1/100000 On/Off
Blacklight Compensation	Built-in
AGC	Built-in
Lens Mount	Standard F3.6mm lens
Lens Option	2.5mm/4mm/6mm/8mm/12mm
Power	DC12V
Power Consumption	110mA
Operating Circumstance	Temperature:-10℃~+50℃
	Humidity: Within 30~90% RH
Dimension(mm)	(Φ)100x60(H)
Weight	275g
Criteria	CE

Dome B/W Camera



FEATURES

- 1/3" B/W CCD
- Minimum Illumination: 0.05Lux
- Horizontal Resolution: 600TV Lines
- Specification

Model	VC-604
Image Device	1/3" B/W CCD
TV System	PAL/NTSC
Effective Pixel	752(H) x 582(V)/768(H)x494(V)
Sync. System	Internal
Scanning System	2:1 Interlace
Grammer	r = 0.45
Scanning Frequency	Horizontal:15.625KHz Vertical:50Hz
Horizontal Resolution	600TV Lines
Minimum Illumination	0.05Lux F1.2
Video Output	1.0Vp-p VBS75Ω BNC
Gain	Built-in AGC 30dB; SAGC 36dB
S/N Ration	48dB
Electronic Shutter	1/50~1/100000 On/Off
Blacklight Compensation	Built-in
AGC	Built-in
Lens Mount	Standard F3.6mm lens
Lens Option	2.5mm/4mm/6mm/8mm/12mm
Power	DC12V
Power Consumption	150mA
Operating Circumstance	Temperature:-10℃~+50℃
	Humidity: Within 30~90% RH
Dimension(mm)	Φ118x77H
Weight	268g
Criteria	CE

Dome B/W Camera



FEATURES

- 1/3" B/W CCD
- Mini-Dome Camera
- Minimum Illumination: 0.05Lux
- Horizontal Resolution: 420TV Lines
- Specification

Model	VC-600D
Image Device	1/3" B/W CCD
TV System	PAL/NTSC
Effective Pixel	500(H) x 582(V)/510(H) x 493(V)
SYNC System	Internal
Scanning System	2:1 Interlace
Gamma	$r = 0.45$
Scanning Frequency	Horizontal:15.625KHz Vertical:50Hz
Horizontal Resolution	420TV Lines
Minimum Illumination	0.05Lux F2.0
Video Output	1.0Vp-p VBS75Ω BNC
Gain	Built-in AGC 30dB; SAGC 36dB
S/N Ratio	50dB
Electronic Shutter	1/50,1/60~1/100000 Sec
Blacklight Compensation	Built-in
AGC	Built-in
Current Consumption	≤100mA
Power	DC12V
Pinhole Lens Mount	F3.7mm Standard (115° (Diagonal),F2.5 Option)
Operating Circumstance	Temperature:-10°C~+50°C
	Humidity: Within 30~90% RH
Dimension(mm)	48(Φ)x42.5(H)
Weight	148g
Criteria	CE

Dome B/W Camera



FEATURES

- 1/3" B/W CCD
- Mini-Dome Camera
- Minimum Illumination: 0.05Lux
- Horizontal Resolution: 420TV Lines
- Specification

Model	VC-601D
Image Device	1/3" B/W CCD
TV System	PAL/NTSC
Effective Pixel	500(H) x 582(V)/510(H) x 493(V)
SYNC System	Internal
Scanning System	2:1 Interlace
Gamma	$\gamma = 0.45$
Scanning Frequency	Horizontal:15.625KHz Vertical:50Hz
Horizontal Resolution	420TV Lines
Minimum Illumination	0.05Lux F2.0
Video Output	1.0Vp-p VBS75Ω BNC
Gain	Built-in AGC 30dB; SAGC 36dB
S/N Ratio	50dB
Electronic Shutter	1/50,1/60~1/100000 Sec
Blacklight Compensation	Built-in
AGC	Built-in
Current Consumption	≤100mA
Power	DC12V
Pinhole Lens Mount	F3.7mm Standard (115° (Diagonal),F2.5 Option)
Operating Circumstance	Temperature:-10°C~+50°C
	Humidity: Within 30~90% RH
Dimension(mm)	64.5(Φ)x42.5(H)
Weight	148g
Criteria	CE

Dome Color Camera



FEATURES

- 1/3" or 1/4" Color Sharp CCD Dome Camera
- Minimum Illumination: 0.5Lux
- Horizontal Resolution: 420TV Lines
- Specification

Model	VC-702	VC-702S
Image Device	1/4" Color Sharp CCD	1/3" Color Sony CCD
TV System	PAL/NTSC	
Effective Pixel	500(H) x 582(V)/510(H) x 493(V)	
SYNC System	Internal	
Scanning System	2:1 Interlace	
Gamma	$\gamma = 0.45$	
Scanning Frequency	Horizontal:15.625KHz Vertical:50Hz	
Horizontal Resolution	420TV Lines	
Minimum Illumination	0.5Lux F2.0	
Video Output	1.0Vp-p VBS75Ω BNC	
Gain	Built-in AGC 30dB; SAGC 36dB	
S/N Ratio	45dB	
Electronic Shutter	1/50,1/60~1/100000 Sec	
Blacklight Compensation	Built-in	
AGC	Built-in	
Current Consumption	120mA	
Power	DC12V	
Lens Mount	f3.6mm Standard(f 6,8,12mm Option)	
Operating Circumstance	Temperature:-10℃~+50℃	
	Humidity: Within 30~90% RH	
Dimension(mm)	(Φ)100x60(H)	
Weight	275	
Criteria	CE	

Dome Color Camera



FEATURES

- 1/3" Color CCD Dome Camera
- Minimum Illumination: 0.5Lux
- Horizontal Resolution: 530TV Lines
- Specification

Model	VC-703S	VC-703SH
Image Device	1/3" Color Sony CCD	
TV System	PAL/NTSC	
Effective Pixel	500(H) x 582(V)/510(H) x 493(V)	795(H) x 596 (V)
SYNC System	Internal	
Scanning System	2:1 Interlace	
Grammer	r = 0.45	
Scanning Frequency	Horizontal:15.625KHz Vertical:50Hz	
Horizontal Resolution	420TV Lines	530TVL
Minimum Illumination	0.5Lux F2.0	
Video Output	1.0Vp-p VBS75Ω BNC	
Gain	Built-in AGC 30dB; SAGC 36dB	
S/N Ration	45dB	
Electronic Shutter	1/50,1/60~1/100000 Sec	
Blacklight Compensation	Built-in	
AGC	Built-in	
Current Consumption	120mA	
Power	DC12V	
Lens Mount	f3.6mm Standard(f 6,8,12mm Option)	
Operating Circumstance	Temperature:-10℃~+50℃	
	Humidity: Within 30~90% RH	
Dimension(mm)	(Φ)128x100(H)	
Weight	285g	
Criteria	CE	

Dome Color Camera



FEATURES

- 1/3" or 1/4" Color CCD
- IR Dome Camera
- Minimum Illumination: 0.Lux
- Horizontal Resolution: 420TV Lines
- Specification

Model	VC-705S	VC-705
Image Device	1/3" Color Sony CCD	1/4"Color Sharp CCD
TV System	PAL/NTSC	
Effective Pixel	500(H) x 582(V)/510(H) x 493(V)	
SYNC System	Internal	
Scanning System	2:1 Interlace	
Grammer	$r = 0.45$	
Scanning Frequency	Horizontal:15.625KHz Vertical:50Hz	
Horizontal Resolution	420TV Lines	
Minimum Illumination	0Lux F2.0(Infra-red Range $\geq 15m$) 18 LED	
Video Output	1.0Vp-p VBS75 Ω BNC	
Gain	Built-in AGC 30dB; SAGC 36dB	
S/N Ration	45dB	
Electronic Shutter	1/50,1/60~1/100000 Sec	
Blacklight Compensation	Built-in	
AGC	Built-in	
Current Consumption	120mA	
Power	DC12V	
Lens Mount	f3.6mm Standard(f 6,8,12mm Option)	
Operating Circumstance	Temperature:-10 $^{\circ}$ C~+50 $^{\circ}$ C	
	Humidity: Within 30~90% RH	
Dimension(mm)	(Φ)114x80(H)	
Weight	240g	
Criteria	CE	

Dome Color Camera



FEATURES

- 1/3" or 1/4" Color CCD
- IR Dome Camera
- Minimum Illumination: 0. Lux
- Horizontal Resolution: 420TV Lines
- Specification

Model	VC-706S	VC-706
Image Device	1/3" Color Sony CCD	1/4" Color Sharp CCD
TV System	PAL/NTSC	
Effective Pixel	500(H) x 582(V)/510(H) x 493(V)	
SYNC System	Internal	
Scanning System	2:1 Interlace	
Grammer	$r = 0.45$	
Scanning Frequency	Horizontal:15.625KHz Vertical:50Hz	
Horizontal Resolution	420TV Lines	
Minimum Illumination	0Lux F2.0(Infra-red Range $\geq 10m$) 12 LED	
Video Output	1.0Vp-p VBS75 Ω BNC	
Gain	Built-in AGC 30dB; SAGC 36dB	
S/N Ration	45dB	
Electronic Shutter	1/50,1/60~1/100000 Sec	
Blacklight Compensation	Built-in	
AGC	Built-in	
Current Consumption	120mA	
Power	DC12V	
Lens Mount	f3.6mm Standard(f 6,8,12mm Option)	
Operating Circumstance	Temperature:-10 $^{\circ}$ C~+50 $^{\circ}$ C	
	Humidity: Within 30~90% RH	
Dimension(mm)	(Φ)93x73(H)	
Weight	220g	
Criteria	CE	

Dome Color Camera



FEATURES

- 1/3" or 1/4" Color CCD Dome Camera
- Minimum Illumination: 0.5 Lux
- Horizontal Resolution: 420TV Lines
- Specification

Model	VC-707S	VC-707
Image Device	1/3" Color Sony CCD	1/4" Color Sharp CCD
TV System	PAL/NTSC	
Effective Pixel	500(H) x 582(V)/510(H) x 493(V)	
SYNC System	Internal	
Scanning System	2:1 Interlace	
Grammer	$r = 0.45$	
Scanning Frequency	Horizontal: 15.625KHz Vertical: 50Hz	
Horizontal Resolution	420TV Lines	
Minimum Illumination	0.5Lux F2.0	
Video Output	1.0Vp-p VBS75Ω BNC	
Gain	Built-in AGC 30dB; SAGC 36dB	
S/N Ration	45dB	
Electronic Shutter	1/50, 1/60~1/100000 Sec	
Blacklight Compensation	Built-in	
AGC	Built-in	
Current Consumption	120mA	
Power	DC12V	
Lens Mount	f3.6mm Standard(f 6,8,12mm Option)	
Operating Circumstance	Temperature: -10°C~+50°C	
	Humidity: Within 30~90% RH	
Dimension(mm)	(Φ)109x75(H)	
Weight	220g	
Criteria	CE	

Dome Color Camera



FEATURES

- 1/3" or 1/4" Color CCD
- IR Dome Camera
- Minimum Illumination: 0.Lux
- Horizontal Resolution: 420TV Lines
- Specification

Model	VC-708S	VC-708
Image Device	1/3" Color Sony CCD	1/4"Color Sharp CCD
TV System	PAL/NTSC	
Effective Pixel	500(H) x 582(V)/510(H) x 493(V)	
SYNC System	Internal	
Scanning System	2:1 Interlace	
Grammer	$r = 0.45$	
Scanning Frequency	Horizontal:15.625KHz Vertical:50Hz	
Horizontal Resolution	420TV Lines	
Minimum Illumination	0Lux F2.0(Infra-red Range $\geq 15m$) 18 LED	
Video Output	1.0Vp-p VBS75 Ω BNC	
Gain	Built-in AGC 30dB; SAGC 36dB	
S/N Ration	45dB	
Electronic Shutter	1/50,1/60~1/100000 Sec	
Blacklight Compensation	Built-in	
AGC	Built-in	
Current Consumption	120mA	
Power	DC12V	
Lens Mount	f3.6mm Standard(f 6,8,12mm Option)	
Operating Circumstance	Temperature:-10 $^{\circ}$ C~+50 $^{\circ}$ C	
	Humidity: Within 30~90% RH	
Dimension(mm)	(Φ)114x80(H)	
Weight	240g	
Criteria	CE	

Dome Color Camera




FEATURES

- 1/3" or 1/4" Color CCD
- IR Dome Camera
- Minimum Illumination: 0. Lux
- Horizontal Resolution: 420TV Lines
- Specification

Model	VC-709S	VC-709
Image Device	1/3" Color Sony CCD	1/4" Color Sharp CCD
TV System	PAL/NTSC	
Effective Pixel	500(H) x 582(V)/510(H) x 493(V)	
SYNC System	Internal	
Scanning System	2:1 Interlace	
Grammer	r = 0.45	
Scanning Frequency	Horizontal:15.625KHz Vertical:50Hz	
Horizontal Resolution	420TV Lines	
Minimum Illumination	0Lux F2.0(Infra-red Range $\geq 10m$) 12 LED	
Video Output	1.0Vp-p VBS75 Ω BNC	
Gain	Built-in AGC 30dB; SAGC 36dB	
S/N Ration	45dB	
Electronic Shutter	1/50,1/60~1/100000 Sec	
Blacklight Compensation	Built-in	
AGC	Built-in	
Current Consumption	120mA	
Power	DC12V	
Lens Mount	f3.6mm Standard(f 6,8,12mm Option)	
Operating Circumstance	Temperature:-10 $^{\circ}$ C~+50 $^{\circ}$ C	
	Humidity: Within 30~90% RH	
Dimension(mm)	$(\Phi)101 \times 61(H)$	
Weight	170g	
Criteria	CE	

Dome Color Camera



FEATURES

- 1/3" or 1/4" Color CCD
- Mini-Dome Camera
- Minimum Illumination: 0.5Lux
- Horizontal Resolution: 420TV Lines
- Specification

Model	VC-800D	VC-800D4
Image Device	1/3" Color Sony CCD	1/4" Color Sharp CCD
TV System	PAL/NTSC	
Effective Pixel	500(H) x 582(V)/510(H) x 493(V)	
SYNC System	Internal	
Scanning System	2:1 Interlace	
Gamma	$r = 0.45$	
Scanning Frequency	Horizontal: 15.625KHz Vertical: 50Hz	
Horizontal Resolution	420TV Lines	
Minimum Illumination	0.05Lux/F2.0	
Video Output	1.0Vp-p VBS75Ω BNC	
Gain	Built-in AGC 30dB; SAGC 36dB	
S/N Ratio	45dB	
Electronic Shutter	1/50, 1/60~1/100000 Sec	
Blacklight Compensation	Built-in	
AGC	Built-in	
Current Consumption	180mA	
Power	DC12V	
Pinhole Lens Mount	F3.7mm Standard (115° (Diagonal), F2.5 Option)	
Operating Circumstance	Temperature: -10°C ~ +50°C	
	Humidity: Within 30~90% RH	
Dimension(mm)(LxWxH)	48(Φ)x42.5(H)	
Weight	164g	
Criteria	CE	

Dome Color Camera



FEATURES

- 1/3" or 1/4" Color CCD
- Mini-Dome Camera
- Minimum Illumination: 0.5Lux
- Horizontal Resolution: 420TV Lines
- Specification

Model	VC-801D	VC-801D4
Image Device	1/3" Color Sony CCD	1/4" Color Sharp CCD
TV System	PAL/NTSC	
Effective Pixel	500(H) x 582(V)/510(H) x 493(V)	
SYNC System	Internal	
Scanning System	2:1 Interlace	
Gamma	$\gamma = 0.45$	
Scanning Frequency	Horizontal: 15.625KHz Vertical: 50Hz	
Horizontal Resolution	420TV Lines	
Minimum Illumination	0.05Lux/F2.0	
Video Output	1.0Vp-p VBS75Ω BNC	
Gain	Built-in AGC 30dB; SAGC 36dB	
S/N Ratio	45dB	
Electronic Shutter	1/50, 1/60~1/100000 Sec	
Blacklight Compensation	Built-in	
AGC	Built-in	
Current Consumption	180mA	
Power	DC12V	
Pinhole Lens Mount	F3.7mm Standard (115° (Diagonal), F2.5 Option)	
Operating Circumstance	Temperature: -10°C ~ +50°C	
	Humidity: Within 30~90% RH	
Dimension(mm)(LxWxH)	64.5(Φ)x42.5(H)	
Weight(kg)	164g	
Criteria	CE	