

Calculator



- * Calculator Hidden Camera
- * 1/3"Color sony CCD Camera
- * 2.400—2.483Ghz wireless transmitter and receiver
- * Transmit distance: 30-100Meter,50mW(Obstructed / Unobstructed)

Normal Calculator **has a mini-video camera built-in**. Just plug into the wall and your VCR, Monitor or TV with AV input and you're ready to go. Watch your office or living room, your nanny or workman.

◆ SPECIFICATION

Model	VC-8013CACC3
Image Device	1/3" Sony Color CCD
TV System	NTSC/PAL
Effective Pixels	500(H)×582(V)/510(H)×592(V)
Scanning System	2:1 Interlace
Sync.System	Internal
Horizontal Resolution	420TV Lines
Minimum Illumination	0. 5Lux F1.2
Video Output	1.0Vp-p VBS75 Ω
AGC	Built-in
S/N Ratio	45dB
White Balance	Automatic (2,100 ⁰ K~8,000 ⁰ K)
Auto Electronic Shutter	1/50, 1/60~1/100000 Sec Automatic
Lens	90° Standard F3.7mm glass pinhole lens
Power Supply	DC12V 600mA
Audio	Built-in super amplifier Mic
Operating Temperature	-10℃~+50℃
Dimension	255x158x56mm
Gross Weight	1.5kg
Operating Humidity	Within 30~90% RH

* **Included Accessories:AV Cable:1pcs,Power supply:2pcs,Manual:1pc, Antenna:1pc, receiver:1pcs .**

Radio



Radio clock Hidden Camera

* 1/3" Sony color CCD camera

* 2.400—2.483Ghz wireless transmitter and receiver

* Transmit distance: 30-100Meter,50mW(Obstructed / Unobstructed)

Normal radio clock **has a mini-video camera built-in**. Just plug into the wall and your VCR, Monitor or TV with AV input and you're ready to go. Watch your office or living room, your nanny or workman

◆ SPECIFICATION

Model	VC-8014CACC3
Image Device	1/3" Sony Color CCD
TV System	NTSC/PAL
Effective Pixels	500(H)×582(V)/510(H)×592(V)
Scanning System	2:1 Interlace
Sync.System	Internal
Horizontal Resolution	420TV Lines
Minimum Illumination	0. 5Lux F1.2
Video Output	1.0Vp-p VBS75 Ω
AGC	Built-in
S/N Ratio	45dB
White Balance	Automatic (2,100 ⁰ K~8,000 ⁰ K)
Auto Electronic Shutter	1/50, 1/60~1/100000 Sec Automatic
Lens	90° Standard F3.7mm glass pinhole lens
Power Supply	AC90-240V
Audio	Built-in super amplifier Mic
Dimension	170x175x52mm
Gross Weight	1.53kg
Operating Temperature	-10℃~+50℃
Operating Humidity	Within 30~90% RH

*** Included Accessories:AV Cable:1pcs,Power supply:1pcs,Manual:1pc, Antenna:1pc, receiver:1pcs.**

Wooden Radio



- * Wooden radio clock Hidden Camera
- * 1/3"Color sony CCD Camera
- * 2.400—2.483Ghz wireless transmitter and receiver
- * Transmit distance: 30-100Meter,50mW(Obstructed / Unobstructed)

Normal radio clock **has a mini-video camera built-in**. Just plug into the wall and your VCR, Monitor or TV with AV input and you're ready to go. Watch your office or living room, your nanny or workman.

◆ SPECIFICATION

Model	VC-8015CACC3
Image Device	1/3" Sony Color CCD
TV System	NTSC/PAL
Effective Pixels	500(H)×582(V)/510(H)×592(V)
Scanning System	2:1 Interlace
Sync.System	Internal
Horizontal Resolution	420TV Lines
Minimum Illumination	0. 5Lux F1.2
Video Output	1.0Vp-p VBS75 Ω
AGC	Built-in
S/N Ratio	45dB
White Balance	Automatic (2,100 ⁰ K~8,000 ⁰ K)
Auto Electronic Shutter	1/50, 1/60~1/100000 Sec Automatic
Lens	90° Standard F3.7mm glass pinhole lens
Power Supply	DC12V 600mA
Audio	Built-in super amplifier Mic
Dimension	180X90X90mm
Gross Weight	1.55kg
Operating Temperature	-10℃~+50℃
Operating Humidity	Within 30~90% RH

*** Included Accessories:AV Cable:1pcs,Power supply:2pcs,Manual:1pc, Antenna:1pc ,receiver:1pcs.**

Wooden Radio



- * Wooden radio clock Hidden Camera
- * 1/3"Color sony CCD Camera
- * 2.42.400—2.483Ghz wireless transmitter and receiver
- * Transmit distance: 30-100Meter,50mW(Obstructed / Unobstructed)

Normal radio clock **has a mini-video camera built-in**. Just plug into the wall and your VCR, Monitor or TV with AV input and you're ready to go. Watch your office or living room, your nanny or workman.

◆ SPECIFICATION

Model	VC-B8015CACC3
Image Device	1/3" Sony Color CCD
TV System	NTSC/PAL
Effective Pixels	500(H)×582(V)/510(H)×592(V)
Scanning System	2:1 Interlace
Sync.System	Internal
Horizontal Resolution	420TV Lines
Minimum Illumination	0. 5Lux F1.2
Video Output	1.0Vp-p VBS75 Ω
AGC	Built-in
S/N Ratio	45dB
White Balance	Automatic (2,100 ⁰ K~8,000 ⁰ K)
Auto Electronic Shutter	1/50, 1/60~1/100000 Sec Automatic
Lens	90° Standard F3.7mm glass pinhole lens
Power Supply	DC12V 600mA
Audio	Built-in super amplifier Mic
Dimension	230X115X105mm
Gross Weight	1.7kg
Operating Temperature	-10℃~+50℃
Operating Humidity	Within 30~90% RH

* **Included Accessories:AV Cable:1pcs,Power supply:2pcs,Manual:1pc, Antenna:1pc ,receiver:1pcs .**

Oval Clock



Oval Clock Hidden Camera

- * 1/3"Color sony CCD Camera
- * 2.400—2.483Ghz wireless transmitter and receiver
- * Transmit distance: 30-100Meter,50mW(Obstructed / Unobstructed)
- * Optional rechargeable Li-ion battery Remote control

Normal clock **has a mini-video camera built-in**. Just plug into the wall and your VCR, Monitor or TV with AV input and you're ready to go. Watch your office or living room, your nanny or workman.

◆ SPECIFICATION

Model	VC-8016CACC3
Image Device	1/3" Sony Color CCD
TV System	NTSC/PAL
Effective Pixels	500(H)×582(V)/510(H)×592(V)
Scanning System	2:1 Interlace
Sync.System	Internal
Horizontal Resolution	420TV Lines
Minimum Illumination	0. 5Lux F1.2
Video Output	1.0Vp-p VBS75 Ω
AGC	Built-in
S/N Ratio	45dB
White Balance	Automatic (2,100 ⁰ K~8,000 ⁰ K)
Auto Electronic Shutter	1/50, 1/60~1/100000 Sec Automatic
Lens	90° Standard F3.7mm glass pinhole lens
Power Supply	AC90-240V
Audio	Built-in super amplifier Mic
Dimension	165x260x27mm
Gross Weight	1.45kg
Operating Temperature	-10℃~+50℃
Operating Humidity	Within 30~90% RH

*** Included Accessories:AV Cable:1pcs,Power supply:1pcs,Manual:1pc, Antenna:1pc, receiver:1pcs.**

Wall Clock



- * Wall Clock Hidden Camera
- * 1/3"Color sony CCD Camera
- * 2.400—2.483Ghz wireless transmitter and receiver
- * Transmit distance: 30-100Meter,50mW(Obstructed / Unobstructed)
- * Optional rechargeable Li-ion battery Remote control

Normal Wall Clock **has a mini-video camera built-in**. Just plug into the wall and your VCR, Monitor or TV with AV input and you're ready to go. Watch your office or living room, your nanny or workman.

◆ SPECIFICATION

Model	VC-8017CACC3
Image Device	1/3" Sony Color CCD
TV System	NTSC/PAL
Effective Pixels	500(H)×582(V)/510(H)×592(V)
Scanning System	2:1 Interlace
Sync.System	Internal
Horizontal Resolution	420TV Lines
Minimum Illumination	0. 5Lux F1.2
Video Output	1.0Vp-p VBS75 Ω
AGC	Built-in
S/N Ratio	45dB
White Balance	Automatic (2,100 ⁰ K~8,000 ⁰ K)
Auto Electronic Shutter	1/50, 1/60~1/100000 Sec Automatic
Lens	90° Standard F3.7mm glass pinhole lens
Power Supply	DC12V 600mA
Audio	Built-in super amplifier Mic
Dimension	∅ 300x40mm
Gross Weight	1.61
Operating Temperature	-10℃~+50℃
Operating Humidity	Within 30~90% RH

*** Included Accessories:AV Cable:1pcs,Power supply:2pcs,Manual:1pc, Antenna:1pc, receiver:1pcs.**

Socket



- * Socket Hidden Camera
- * 1/3" Sony color CCD camera
- * 2.400—2.483Ghz wireless transmitter and receiver
- * Transmit distance: 30-100Meter,50mW(Obstructed / Unobstructed)

Normal Socket **has a mini-video camera built-in**. Just plug into the wall and your VCR, Monitor or TV with AV input and you're ready to go. Watch your office or living room, your nanny or workman

◆ SPECIFICATION

Model	VC-8019CACC3
Image Device	1/3" Sony Color CCD
TV System	NTSC/PAL
Effective Pixels	500(H)×582(V)/510(H)×592(V)
Scanning System	2:1 Interlace
Sync.System	Internal
Horizontal Resolution	420TV Lines
Minimum Illumination	0. 5Lux F1.2
Video Output	1.0Vp-p VBS75 Ω
AGC	Built-in
S/N Ratio	45dB
White Balance	Automatic (2,100 ⁰ K~8,000 ⁰ K)
Auto Electronic Shutter	1/50, 1/60~1/100000 Sec Automatic
Lens	90° Standard F3.7mm glass pinhole lens
Power Supply	AC90-240V
Audio	Built-in super amplifier Mic
Dimension	54x80x48mm
Gross Weight	1.1kg
Operating Temperature	-10℃~+50℃
Operating Humidity	Within 30~90% RH

*** Included Accessories:AV Cable:1pcs,Power supply:1pcs,Manual:1pc, Antenna:1pc, receiver:1pcs .**

Pencil vase



- * pencil vase Hidden Camera
- * 1/3"Color sony CCD Camera
- * 2.400—2.483Ghz wireless transmitter and receiver
- * Transmit distance: 30-100Meter,50mW(Obstructed / Unobstructed)
- * Optional rechargeable Li-ion battery Remote control

Normal pencil vase and Desk clock **has a mini-video camera built-in**. Just plug into the wall and your VCR, Monitor or TV with AV input and you're ready to go. Watch your office or living room, your nanny or workman.

◆ SPECIFICATION

Model	VC-8052CACCC3
Image Device	1/3" Sony Color CCD
TV System	NTSC/PAL
Effective Pixels	500(H)×582(V)/510(H)×592(V)
Scanning System	2:1 Interlace
Sync.System	Internal
Horizontal Resolution	420TV Lines
Minimum Illumination	0. 5Lux F1.2
Video Output	1.0Vp-p VBS75 Ω
AGC	Built-in
S/N Ratio	45dB
White Balance	Automatic (2,100 ⁰ K~8,000 ⁰ K)
Auto Electronic Shutter	1/50, 1/60~1/100000 Sec Automatic
Lens	90° Standard F3.7mm glass pinhole lens
Power Supply	DC12V 600mA
Audio	Built-in super amplifier Mic
Dimension	80×115×90mm
Gross Weight	1.52kg
Operating Temperature	-10℃~+50℃
Operating Humidity	Within 30~90% RH

*** Included Accessories:AV Cable:1pcs,Power supply:2pcs,Manual:1pc, Antenna:1pc ,receiver:1pcs.**

Desk colock



- * Desk colock hidden camera
- * 1/3"Color sony CCD Camera
- * 2.400—2.483Ghz wireless transmitter and receiver
- * Transmit distance: 30-100Meter,50mW(Obstructed / Unobstructed)

Normal Desk clock **has a mini-video camera built-in**. Just plug into the wall and your VCR, Monitor or TV with AV input and you're ready to go. Watch your office or living room, your nanny or workman.

◆ SPECIFICATION

Model	VC-8037CACC3
Image Device	1/3" Sony Color CCD
TV System	NTSC/PAL
Effective Pixels	500(H)×582(V)/510(H)×592(V)
Scanning System	2:1 Interlace
Sync.System	Internal
Horizontal Resolution	420TV Lines
Minimum Illumination	0. 5Lux F1.2
Video Output	1.0Vp-p VBS75Ω
AGC	Built-in
S/N Ratio	45dB
White Balance	Automatic (2,100 ⁰ K~8,000 ⁰ K)
Auto Electronic Shutter	1/50, 1/60~1/100000 Sec Automatic
Lens	90° Standard F3.7mm glass pinhole lens
Power Supply	DC12V 600mA
Audio	Built-in super amplifier Mic
Dimension	115×130×40(mm)
Gross Weight	1.35kg
Operating Temperature	-10℃~+50℃
Operating Humidity	Within 30~90% RH

*** Included Accessories:AV Cable:1pcs,Power supply:2pcs,Manual:1pc, Antenna:1pc ,receiver:1pcs .**

Desk colock



- * Desk clock hidden camera
- * 1/3"Color sony CCD Camera
- * 2.400—2.483Ghz wireless transmitter and receiver
- * Transmit distance: 30-100Meter,50mW(Obstructed / Unobstructed)
- * Optional rechargeable Li-ion battery Remote control

Normal Desk clock **has a mini-video camera built-in**. Just plug into the wall and your VCR, Monitor or TV with AV input and you're ready to go. Watch your office or living room, your nanny or workman.

◆ SPECIFICATION

Model	VC-8012CACC3
Image Device	1/3" Sony Color CCD
TV System	NTSC/PAL
Effective Pixels	500(H)×582(V)/510(H)×592(V)
Scanning System	2:1 Interlace
Sync.System	Internal
Horizontal Resolution	420TV Lines
Minimum Illumination	0. 5Lux F1.2
Video Output	1.0Vp-p VBS75 Ω
AGC	Built-in
S/N Ratio	45dB
White Balance	Automatic (2,100 ⁰ K~8,000 ⁰ K)
Auto Electronic Shutter	1/50, 1/60~1/100000 Sec Automatic
Lens	90° Standard F3.7mm glass pinhole lens
Power Supply	DC12V 600mA
Audio	Built-in super amplifier Mic
Dimension	135×95×65mm
Gross Weight	1.456kg
Operating Temperature	-10℃~+50℃
Operating Humidity	Within 30~90% RH

*** Included Accessories:AV Cable:1pcs,Power supply:2pcs,Manual:1pc, Antenna:1pc, receiver:1pcs .**

Smoke Detector Hidden Camera



- * Smoke Detector Hidden Camera
- * 1/3"Color sony CCD Camera
- * 2.400—2.483Ghz wireless transmitter and receiver
- * Transmit distance: 30-100Meter,50mW(Obstructed / Unobstructed)

This good looking smoke **has a mini-video camera built-in**. Just plug into the wall and your VCR, Monitor or TV with AV input and you're ready to go. Watch your office or living room, your nanny or workman.

◆ SPECIFICATION

Model	VC-8098CACC3
Image Device	1/3" Sony Color CCD
TV System	NTSC/PAL
Effective Pixels	500(H)×582(V)/510(H)×592(V)
Scanning System	2:1 Interlace
Sync.System	Internal
Horizontal Resolution	420TV Lines
Minimum Illumination	0. 5Lux F1.2
Video Output	1.0Vp-p VBS75Ω
AGC	Built-in
S/N Ratio	45dB
White Balance	Automatic (2,100 ⁰ K~8,000 ⁰ K)
Auto Electronic Shutter	1/50, 1/60~1/100000 Sec Automatic
Lens	90° Standard F3.7mm glass pinhole lens
Power Supply	DC12V 600mA
Audio	Built-in super amplifier Mic
Dimension	Φ 110mm × 50mm
Gross Weight	1.356kg
Operating Temperature	-10℃~+50℃
Operating Humidity	Within 30~90% RH

*** Included Accessories:AV Cable:1pcs,Power supply:2pcs,Manual:1pc, Antenna:1pc, receiver:1pcs .**

PIR Detector Hidden Camera



* PIR **Detector** Hidden Camera

* 1/3"Color sony CCD Camera

* 2.400—2.483Ghz wireless transmitter and receiver

* Transmit distance: 30-100Meter,50mW(Obstructed / Unobstructed)

* Optional rechargeable Li-ion battery Remote control

This good looking PIR **Detector** has a **mini-video camera built-in**. Just plug into the wall and your VCR, Monitor or TV with AV input and you're ready to go. Watch your office or living room, your nanny or workman.

◆ SPECIFICATION

Model	VC-8097CACC3
Image Device	1/3" Sony Color CCD
TV System	NTSC/PAL
Effective Pixels	500(H)×582(V)/510(H)×592(V)
Scanning System	2:1 Interlace
Sync.System	Internal
Horizontal Resolution	420TV Lines
Minimum Illumination	0. 5Lux F1.2
Video Output	1.0Vp-p VBS75 Ω
AGC	Built-in
S/N Ratio	45dB
White Balance	Automatic (2,100 ⁰ K~8,000 ⁰ K)
Auto Electronic Shutter	1/50, 1/60~1/100000 Sec Automatic
Lens	90° Standard F3.7mm glass pinhole lens
Power Supply	DC12V 600mA
Audio	Built-in super amplifier Mic
Dimension	110mmx74mmx62mm
Gross Weight	1.35kg
Operating Temperature	-10℃~+50℃
Operating Humidity	Within 30~90% RH

* **Included Accessories:AV Cable:1pcs,Power supply:2pcs,Manual:1pc, Antenna:1pc, receiver:1pcs.**

Smoke Detector Hidden Camera

Remote Control



Smoke detector Hidden Camera

- * 1/3"Color sony CCD Camera
- * 2.400—2.483Ghz wireless transmitter and receiver
- * Transmit distance: 30-100Meter,50mW(Obstructed / Unobstructed)
- * Optional rechargeable Li-ion battery Remote control

This good looking smoke **has a mini-video camera built-in**. Just plug into the wall and your VCR, Monitor or TV with AV input and you're ready to go. Watch your office or living room, your nanny or workman.

◆ SPECIFICATION

Model	VC-8099CACC3
Image Device	1/3" Sony Color CCD
TV System	NTSC/PAL
Effective Pixels	500(H)×582(V)/510(H)×592(V)
Scanning System	2:1 Interlace
Sync.System	Internal
Horizontal Resolution	420TV Lines
Minimum Illumination	0. 5Lux F1.2
Video Output	1.0Vp-p VBS75 Ω
AGC	Built-in
S/N Ratio	45dB
White Balance	Automatic (2,100 ⁰ K~8,000 ⁰ K)
Auto Electronic Shutter	1/50, 1/60~1/100000 Sec Automatic
Lens	90° Standard Red F3.7mm glass pinhole lens
Power Supply	DC12V 600mA
Audio	Built-in super amplifier Mic
Dimension	Φ107mm×33mm
Gross Weight	1.356kg
Operating Temperature	-10℃~+50℃
Operating Humidity	Within 30~90% RH

*** Included Accessories:AV Cable:1pcs,Power supply:2pcs,Manual:1pc, Antenna:1pc, receiver:1pcs .**